



SlowStop® 3" IronFlex Single Railing (SS3Y-25-SFx-x)

4' CENTERS

2,376 Joules (min.) | 4,000# @ 3.6 mph without damage



SS3Y-25-SFL-4



SS3Y-25-SFM-4



SS3Y-25-SFR

6' CENTERS

2,016 Joules (min.) | 4,000# @ 3.3 mph



SS3Y-25-SFL-6



SS3Y-25-SFM-6



SS3Y-25-SFR

8' CENTERS

1,836 Joules (min.) | 4,000# @ 3.2 mph



SS3Y-25-SFL-8



SS3Y-25-SFM-8



SS3Y-25-SFR

- 25" Tall Railing Sections
- Easy connect set screw installation
- Mix and match needed lengths
- Field customizable cut for odd lengths

- Patented Rebounding Steel Construction
- Temperature Rating: -40°F
- Pipe Coating: Galvanized + Polyester Powder Coat
- Base Coating: Environmentally Friendly Water-Based KTL Coating + Polyester Powder Coat



4955 Stout Dr. • San Antonio, TX 78219
210-736-4477 • 800-736-5256 • Fax 210-734-6448
Email: info@slowstop.com
www.slowstop.com



QR: Download Spec Sheets
©2017 SlowStop. All rights reserved. 01/19/2017