



SlowStop® IronFlex Rack End Guard—4” (SS4Y-REP-xx)

45° IMPACT STOPPING POWER

MASS (LBS)	SPEED (MPH)
3,000	10.5
5,000	8.2
10,000	5.8
15,000	4.7

Color: RAL 1023 Yellow Bollard on RAL 9005 Black Base

Diameter: 4” (3.5” Schedule 40 Steel)

Height: 7.25” to Centerline (9.5” Overall)

Width:	42”	SS4Y-REP-42
	34”	SS4Y-REP-44
	96”	SS4Y-REP-96
	98”	SS4Y-REP-98

Max Tilt: 3”



Installs with eight (8) Concrete Anchor Screws



SPECIFICATIONS

- Stopping Power Rating: 10,851 joules / 7,868 ft-lbs. @ 90° Impact
- Temperature Rating: -40°
- Pipe Coating: Galvanized + Polyester Powder Coat
- Base Coating: Environmentally Friendly Water-Based KTL Coating + Polyester Powder Coat

RECOMMENDED USES

- Pallet and Storage Rack Ends
- Heavy fork lift traffic
- Concrete Floors
- Warehouses and Manufacturing Facilities
- Loading Dock Bays (wheel guides)



4955 Stout Dr. • San Antonio, TX 78219
210-736-4477 • 800-736-5256 • Fax 210-734-6448
Email: info@slowstop.com
www.slowstop.com



QR: Download Spec Sheets
©2020 SlowStop. All rights reserved.